

Wiggins Mill Water Treatment Facility P.O. Box 10 Wilson, NC 27894









Improvements Coming to Lake Wilson

Lake Wilson has been around for a long time. It has been used for many different purposes throughout its history, such as a sawmill and grain mill. Since around 1961, its primary use is for impoundment of our drinking water supply. This is also when the present day dam was constructed. At almost 60 years old, the dam is in need of some renovations and repairs. It is still structurally sound, but the control gates are showing their age. The present work will replace the gates and allow for some concrete repairs. Along with this work are some major upgrades to the Lake's surroundings in the recreational sense. The new 1,000-foot walking bridge is complete, allowing a 2.25 mile circle around the lake. New ADA compliant parking, kayak launch, and bathroom facility are a sample of what is to come. Improvements to the boat launch, docks, and overall parking are also planned. Please visit www.wilsonnc.org to see all of the great improvements planned for Lake Wilson Park



Renovation and repair of dam




Completion of 1,000 foot walking bridge

City of Wilson's Source Waters

Cryptosporidium

Our system monitored for Cryptosporidium during 2018 and had detections in one sample at Wiggins Mill Reservoir for an average of 0.021 oocysts/Liter and detections in three samples at Toisnot Reservoir for an average of 0.032 oocysts/Liter. Cryptosporidium is a microbial pathogen found in surface water throughout the U.S. Although filtration removes Cryptosporidium, the most commonly-used filtration methods cannot guarantee 100 percent removal. Our monitoring indicates the presence of these organisms in our source water and/or finished water. Current test methods do not allow us to determine if the organisms are dead or if they are capable of causing disease. Ingestion of Cryptosporidium may cause cryptosporidiosis, an abdominal infection. Symptoms of infection include nausea, diarrhea, and abdominal cramps. Most healthy individuals can overcome the disease within a few weeks. However, immuno-compromised people, infants and small children, and the elderly are at greater risk of developing life-threatening illness. We encourage immuno-compromised individuals to consult their doctor regarding appropriate precautions to take to avoid infection. Cryptosporidium must be ingested to cause disease, and it may be spread through means other than drinking water.



The City of Wilson obtains its water supply from two sources. The first source is Contentnea Creek and consists of the Buckhorn Lake and the downstream Wiggins Mill Reservoir. Buckhorn Lake is the City's largest water supply reservoir and is an impoundment on the Contentnea Creek approximately 12 miles west of the city. Water is released from Buckhorn Lake into Contentnea Creek and is pumped from the downstream Wiggins Mill Reservoir to the Wiggins Mill Water Treatment Plant and to the Toisnot Water Treatment Plant. The other water supply source for the City is Toisnot Reservoir and consists of Lake Wilson and the downstream Toisnot Reservoir, which together provide water for the Toisnot Water Treatment Plant. A connection from the Tar River Reservoir to upstream of Lake Wilson is also available as a water supply during emergency conditions.

Improvement Highlights

- 57 parking spaces total (5 ADA parking spaces)
- ADA kayak launch
- 24 x 40 shelter for 40 people
- 3 stall bathroom with an inclement weather protection area
- 1,000-foot bridge installed to complete loop for walking
 2.25 mile nature path
- Parking for 5 trucks and trailers
- 1 natural playground combo
- Refurbished fishing docks
- ADA compliant sidewalks
- Tree / landscape plantings

- Two grills
- 4 picnic tables
- 12 benches
- 2 swings



PWS ID# NC0498010

2018 City of Wilson Drinking Water Quality Report What the EPA wants you to know

Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. More information about contaminants and potential health effects can be obtained by calling the Environmental Protection Agency's Safe Drinking Water Hotline (800-426-4791).

Some people may be more vulnerable to contaminants in drinking water than the general population. Immuno-compromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk from infections. These people should seek advice about drinking water from their health care providers. EPA/CDC guidelines on appropriate means to lessen the risk of infection by Cryptosporidium and other microbiological contaminants are available from the Safe Drinking Water Hotline (800-426-4791).

If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. The City of Wilson is responsible for providing high quality drinking water, but cannot control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at http://www.epa.gov/ safewater/lead.

The sources of drinking water (both tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs, and wells. As water travels over the surface of the land or through the ground, it dissolves naturally-occurring minerals and, in some cases, radioactive material, and can pick up substances resulting from the presence of animals or from human activity. Contaminants that may be present in source water include microbial contaminants, such as viruses and bacteria, which may come from sewage treatment plants, septic systems, agricultural livestock operations, and wildlife; inorganic contaminants, such as salts and metals, which can be naturally-occurring or result from urban storm water runoff, industrial or domestic wastewater discharges, oil and gas production, mining, or farming; pesticides and herbicides, which may come from a variety of sources such as agriculture, urban storm water runoff, and residential uses; organic chemical contaminants, including synthetic and volatile organic chemicals, which are by-products of industrial processes and petroleum production, and can also come from gas stations, urban storm water runoff, and septic systems; and radioactive contaminants, which can be naturally-occurring or be the result of oil and gas production and mining activities.

In order to ensure that tap water is safe to drink, EPA prescribes regulations which limit the amount of certain contaminants in water provided by public water systems. FDA regulations establish limits for contaminants in bottled water which must provide the same protection for public health.

Source Water Assessment Program (SWAP)

The North Carolina Department of Environment and Natural Resources (DENR), Public Water Supply (PWS) Section, Source Water Assessment Program (SWAP) conducted assessments for all drinking water sources across North Carolina. The purpose of the assessments was to determine the susceptibility of each drinking water source (well or surface water intake) to Potential Contaminant Sources (PCSs). The results of the assessment are available in SWAP Assessment Reports that include maps, background information, and a relative susceptibility rating of Higher, Moderate, or Lower. The relative susceptibility rating of each source of the City of Wilson was determined by combining the contaminant rating (number and location of PCSs within the assessment area) and the inherent vulnerability rating (ie., characteristics or existing conditions of the well or watershed and its delineated assessment area). The assessment findings are summarized in Figure A.



Wiggins Mill

Toisnot

The complete SWAP Assessment report for the City of Wilson may be viewed on the Web at http://www.ncwater.org/pws/swap. Please note that because SWAP results and reports are periodically updated by the PWS Section, the results available on this website may differ from the results that were available at the time this report was prepared. To obtain a printed copy of this report, please mail a written request to: Source Water Assessment Program – Report Request, 1634 Mail Service Center, Raleigh, NC 27699-1634, or e-mail request to swap@ncdenr.gov. Please indicate your system name, PWSID, and provide your name, mailing address, and phone number. If you have any questions about the SWAP report please contact the Source Water Assessment staff by phone at 919-707-9098.

It is important to understand that a susceptibility rating of "higher" does not imply poor water quality, only the systems' potential to become contaminated by PCSs in the assessment area.

For more water quality information:

City of Wilson Water Resources

Wiggins Mill Water Treatment Facility P.O. Box 10, Wilson, NC 27894

Telephone: (252) 399-2378

North Carolina Department of Environmental Quality (NCDEQ)

512 North Salisbury Street

P.O. Box 27687, Raleigh, NC 27611-7867

Telephone: (919) 733-2321

Environmental Protection Agency (EPA)

401 M Street, SW, Washington, DC 20460

Telephone: (202) 260-2090 Safe Drinking Water Hotline Telephone: (800) 426-4791

American Water Works Association (AWWA)

6666 West Quincy Avenue Denver, CO 80235

Telephone: (303) 794-7711

The City of Wilson Water Resources is affiliated with the following organizations: American Water Works Association, North Carolina Water Works Operators Association, North Carolina Rural Water Association, and Water **Environment Federation**

City Council Meetings are held on the third Thursday of each month. Your participation is welcome.

How is the water treated?

Raw water is pumped from either Toisnot Reservoir or Wiggins Mill Reservoir to the treatment facilities. At certain times of the year, the lakes are treated with copper sulfate to limit algae growth which could cause bad tastes and odors. When raw water enters the facility, a substance commonly called ferric sulfate reacts with natural alkalinity, added lime, or sodium hydroxide to cause small particles to cling to one another after strong mixing. Powdered activated carbon is added to control taste and odor causing substances that occur naturally in the raw water. The water is then mixed slowly and another chemical called polymer is added. The particles are then much larger. The water then enters large tanks called settling basins where the heavy particles settle. Other chemicals are added to remove minerals in the filters. The water is then filtered through sand and anthracite to remove remaining fine particles. Chlorine is added to kill harmful bacteria, protozoans, and viruses. Lime or sodium hydroxide and a corrosion inhibitor are added to maintain pH and minimize the potential for corrosion in distribution lines and household plumbing. Fluoride is added to aid in the prevention of tooth decay. The water is then pumped into the distribution system for home, business, and industrial use.

2018 Annual Consumer Confidence Report Information City of Wilson P.O. Box 10 Wilson, NC 27894

City of Wilson's Water Treatment Facilities

Turbidity*								
Contaminant	Treatment Technique (TT) Violation if:		MCLG	Your Water		Likely Source of Contamination	Treatment Technique (TT) Violation Y/N	
Turbidity (NTU)- Highest Measureme	Turbidity >1 NTU		N/A	0.28 NTU				
Turbidity (NTU) - Lowest Monthly Percentage (%) of Samples Meeting Turbidity Limits		Less than 95% of Monthly Turbidity Measurements are ≤ 0.3 NTU		N/A	100%		Soil runoff	NO
*Turbidity is a measure of the samples must be less than or		ater. We monito	r it because it is a	good indicator of the	e effectiveness of or	ur filtration system. Th	ne turbidity rule requires that 95% or more o	f the monthly
Inorganic Contamir	ants							
Contaminant (Units)	Year Sampled	MCL		MCLG	Level Detected	Range Detected	Likely Source of Contamination	MCL Violation Y/N
Fluoride (ppm)	2018	4		4	0.72	0.51 - 0.90	Erosion of natural deposits; water additives which promotes strong teeth; discharge from fertilizer and aluminum factories	NO
Disinfection By-Pro	duct Precurso	ors Contan	ninants					
Contaminant		TT	MCLG	Compliance Method (Step 1 or ACC#)	Level Detected (RAA Removal Ratio)	Range (Monthly Removal Ratio)	Likely Source of Contamination	MCL Violation Y/N
Total Organic Carbon (TOC) (Removal Ratio) - Treated Water		TT	N/A	Step 1	1.6	1.44 - 1.80	Naturally present in the environment	NO

City of Wilson's Distribution System

Stage 2 Disinfection i	Byproduct C	ompliance	-Based upo	on Locational	Running Ann	ual Average (LRAA)	
Disinfection Byproducts	Year Sampled	MCL	MCLG	Your Water (Highest LRAA)	Range Detected	Likely Source of Contamination	MCL Violation Y/N
TTHM (ppb)	2018	80	N/A	65.5	12 - 111	By-product of drinking water disinfection	NO
HAA5 (ppb)	2018	60	N/A	49.0	12 - 70	By-product of drinking water disinfection	NO
	ople who drink wa	ter containing h				s with their liver, kidneys, or central nervous systems, and may ha e an increased risk of getting cancer.	ve an increased
Contaminant (Units)	Year Sampled	MRDL	MRDLG	Your Water (Highest RAA)	Range Detected	Likely Source of Contamination	MRDL Violation Y/N
Chlorine (ppm)	2018	MRDL = 4.0	MRDLG = 4	0.64	0.20 - 1.23	Water additive used to control microbes	NO
Regulated at the Tap	- Lead and (Copper Co	ntaminants				
Contaminant (Units)	Date Last Tested	AL	MCLG	Your Water	Number of Sites Found Above AL	Likely Source of Contamination	MCL Violation Y/N
Lead (ppb) (90 th Percentile)	2016	AL = 15	0	None Detected (90th percentile)	2	Corrosion of household plumbing systems; erosion of natural deposits; leaching from wood preservatives	NO
Copper (ppm) (90 th Percentile)	2016	AL = 1.3	1.3	0.281 (90th percentile)	0	Corrosion of household plumbing systems; erosion of natural deposits; leaching from wood preservatives	

Table Definitions and Key

NA

TT	Treatment Technique- A required process intended to reduce the level of a contaminant in
	drinking water

- AL Action Level-The concentration of a contaminant which, if exceeded, triggers treatment or other requirements which a water system must follow.
- MCL Maximum Contaminant Level- The highest level of a contaminant that is allowed in drinking water. MCLs are set as close to the MCLGs as feasible using the best available treatment technology.
- MCLG Maximum Contaminant Level Goal-The level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs allow for a margin of safety.
- MRDL Maximum Residual Disinfectant Level- The highest level of a disinfectant allowed in drinking water. There is convincing evidence that addition of a disinfectant is necessary for control of microbial contaminants.
- MRDLG Maximum Residual Disinfectant Level Goal-The level of a drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contaminants.

- Not applicable- Information not applicable/not required for that particular water system or for that particular rule.
- **NTU** Nephelometric Turbidity Units- Nephelometric turbidity unit is a measure of the clarity of water. Turbidity in excess of 5 NTU is just noticeable to the average person.
- **ppm** parts per million- One part per million corresponds to one inch in 16 miles.
- **ppb** parts per billion- One part per billion corresponds to one inch in 16,000 miles.
- ppt parts per trillion- One part per trillion would correspond to one square inch in 250 square miles.
- LRAA Locational Running Annual Average-The average of sample analytical results for samples taken at a particular monitoring location during the previous four calendar quarters under the Stage 2 Disinfectants and Disinfection Byproducts Rule.